



AREA -2 / PHASE 1A FIRST FLOOR FRAMING PLAN

- 1.) TOP OF STEEL ELEVATION TO BE 77'-5 3/4" U.N.O. IN PLAN.
- 2.) ALL HSS MATERIAL TO BE A500 - GR. B, ALL ANCHOR ROD MATERIAL TO BE F1554 - GR. 36, ALL ROLLED SHAPES TO BE A992, AND ALL OTHER MATERIAL TO BE A36.
- 3.) ► DENOTES MOMENT CONNECTION. SEE TYPICAL DETAILS.
- 4.) ALL FIELD AND SHOP BOLTS TO BE 3/4" A325X - TC.
- 5.) <NP> = NO PAINT.

3	1/31/05	RELEASE FOR FIELD
2	12/8/04	ADDED PIECE MARKS
1	11/4/04	ADDED PIECE MARKS
REV	DATE	DESCRIPTION

STS STEEL INC.
 ENGINEERS • FABRICATORS • ERECTORS
 PH: (518) 370-2693 FAX: (518) 370-2696

ARCHITECT: JETER, COOK AND JEPSON
CUSTOMER: FLOUR ENTERPRISES INC.
STRUCTURE: HARTFORD HIGH SCHOOL

DETAILED BY: SES **JOB NO. 0406**
CHECKED BY: MS **SHT NO. E2**

BOLTS 3/4" U.N.O.
 HOLES 13/16" U.N.O.
 ELECTRODE E70XXLH
 CLEAN SSPC-SP2 U.N.O.
 PAINT PSI U.N.O.